






## ELECTROMAGNETIC VALVE.

**Publication number:** EP0683862  
**Publication date:** 1995-11-29  
**Inventor:** REITER FERDINAND (DE); MAIER MARTIN (DE);  
HEYSE JOERG (DE); KEIM NORBERT (DE)  
**Applicant:** BOSCH GMBH ROBERT (DE)  
**Classification:**  
**- international:** ***B23K9/04; B23K10/02; F02M51/06; F02M51/08;  
F02M61/16; F02M63/00; B23K9/04; B23K10/02;  
F02M51/06; F02M51/08; F02M61/00; F02M63/00;  
(IPC1-7): F02M51/06***  
**- european:** F02M51/06B1; F02M51/06B2; F02M51/06B2E;  
F02M51/06B2E2B; F02M61/16F; F02M61/16H  
**Application number:** EP19950900661 19941124  
**Priority number(s):** WO1994DE01392 19941124; DE19944421935  
19940623; DE19934341961 19931209

### Also published as:

 WO9516126 (A1)  
 US5732888 (A1)  
 JP2005337266 (A)  
 EP0683862 (A0)  
 BR9406079 (A)


[more >>](#)

[Report a data error here](#)

Abstract not available for EP0683862

Abstract of corresponding document: **US5732888**

PCT No. PCT/DE94/01392 Sec. 371 Date Aug. 9, 1995 Sec. 102(e) Date Aug. 9, 1995 PCT Filed Nov. 24, 1994 PCT Pub. No. WO95/16126 PCT Pub. Date Jun. 15, 1995 An electromagnetically operable valve includes at least one component part, e.g. the armature, which possesses, prior to the application of a wear resistant coating, a wedged surface, which is in each case variably creatable in accordance with a magnetic and hydraulic optimum. The annular impact segment formed by the wedging possesses a defined impact face width or contact width which remains constant throughout the service life, since any wearing of the impact face does not lead, in continuous running, to an enlargement of the contact. The valve is particularly suitable for use in fuel injection systems of explosion-type, spark-ignition combustion engines.



Data supplied from the *esp@cenet* database - Worldwide